



FIRE RESISTANT CERTIFICATE

Light weight PVC coated fabric

TECHNICAL SPECIFICATIONS



WEFT INSERTION
9x9 thread count/in
1000D



BREAKING STRENGTH
WARP: 118 lbf/in \pm 5%
WEFT: 112 lbf/in \pm 5%



TEAR STRENGTH
WARP: 49 lbf \pm 5%
WEFT: 44 lbf \pm 5%



WEIGHT
12 oz/yd² \pm 3%



ADHESION
>11.2 lb/f



ROLL
61" x 54.68 yd



THICKNESS
.012 in \pm 5%

APPLICATIONS

- Industrial Curtains
- Awnings
- Tents

AVAILABLE COLORS



Antimildew (biocide) in white and beige color, it's flame resistant based on CSFM certification F-88801



Ask for new color development.

*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.

 **TOLL FREE (866) 973 7185**

 **salesteam@plasticfabrics.com**

 **www.plasticfabrics.com**

   **/Plastic Fabric Solutions INC**



Certificate No: SG 20201851.01

*Images shown are for reference of the final product, Plastic Fabric Solutions does not certify they represent our final product. - Optimal usage and maintenance are responsibility of the final user to preserve product integrity and utility. - Validity 2021-2022