

Specification sheet DF 38

Autorizated by:
Control Number:
Consecutive:
Emission Date:

Page:

Ma. Esther Sánchez Quality Assurement QA-SS-001

0

0 26-July-2021 1 de 1

Base .	fabric	
--------	--------	--

Style:	Plain weaving: 14 x 14 1000 Denier	Fiber:	Polyester
Count:	14 X 14 thread/inc ó 5.5 x 5.5 thread/cm	Denier:	1000

Properties:		Unit:	Specification:	Unit:	Specification:
Weight		Gr/m²	1300 ± 4 %	Oz/Yd²	38 ± 4 %
Breaking Strength (1)	Warp	Kgf/cm²	37 ± 5 %	Lb/in²	207 ± 5 %
	Weft	Kgf/cm²	36 ± 5 %	Lb/in²	202 ± 5 %
Tear Strength (1)	Warp	Kgf	25 ± 5 %	Lb	55 ± 5 %
	Weft	Kgf	23 ± 5 %	Lb	51 ± 5 %
Adhesion ⁽²⁾		Kgf/cm²	> 3.0	Lb/in²	> 16.8
Thickness ⁽²⁾		mm	1.00 ± 3 %	in	.0394 ± 3 %

Physical Specifications for rolls		Roll Length:
	61 inches	33.16 lineal yards

UV Protector	
This product has a UV protector in all its colors.	

Packaging Specifications:

Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping

The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).

This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.

Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.

To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. fort more information please call us, toll free (866) 973 7185

Non Controlled Document