



**PLASTIC
FABRIC
SOLUTIONS**
by MEGAPLAST

Specification sheet EC 12

Authorized by: Ma. Esther Sánchez
Control Number: QA-SS-005
Consecutive: 0
Emission Date: 26-July-2021
Page: 1 of 1



Registration Number

F - 88801

Base fabric

Style:	Weft Insertion: 9 x 9 1000 Denier	Fiber:	Polyester
Count:	9 X 9 thread/inc ó 5.5 x 5.5 thread/cm	Denier:	1000

Properties:	Unit:	Specification:	Unit:	Specification:
Weight	Gr/m ²	400 ± 3 %	Oz/Yd ²	12 ± 3 %
Breaking Strength (1)	Warp	Kgf/cm ²	Lb/in ²	118 ± 5 %
	Weft	Kgf/cm ²	Lb/in ²	112 ± 5 %
Tear Strength (1)	Warp	Kgf	Lb	49 ± 5 %
	Weft	Kgf	Lb	44 ± 5 %
Flammability Testing*	NFPA-701	The specimen shall not continue to flame for more than two seconds		
Adhesion (2)	Kgf/cm ²	> 2.0	Lb/in ²	> 11.2
Thickness (2)	mm	.30 ± 5 %	in	.012 ± 5 %

Physical Specifications for rolls:	Roll Width	Roll Length:
	61 inches	54.68 lineal yards

UV Protector
 This product has a UV protector in all its colors.

Special Additives
 This product may include fungicide retardant (biocide) in white and beige color, and may include flame retardant based on CSFM certification F-88801

Packaging Specifications:
 Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping

The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).

This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.

Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.

To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. For more information please call us, toll free (866) 973 7185

Non Controlled Document