



Specification sheet FF 18

Autorized by:	Ma. Esther Sánchez
Control Number:	Quality Assurance QA-SS-002
Consecutive:	0
Emission Date:	26-July-2021
Page:	1 de 1

Base fabric

Style:	Plain weaving: 14 x 14 1000 Denier	Fiber:	Polyester
Count:	14 X 14 thread/inc ó 5.5 x 5.5 thread/cm	Denier:	1000

Properties:	Unit:	Specification:	Unit:	Specification:
Weight	Gr/m ²	610 ± 3 %	Oz/Yd ²	18 ± 3 %
Breaking Strength (1)	Warp	Kgf/cm ²		185 ± 5 %
	Weft	Kgf/cm ²		174 ± 5 %
Tear Strength (1)	Warp	Kgf	Lb	90 ± 5 %
	Weft	Kgf	Lb	86 ± 5 %
Adhesion (2)	Kgf/cm ²	> 3.5	Lb/in ²	> 19.6
Thickness (2)	mm	.49 ± 5 %	in	.019 ± 5 %

Physical Specifications for rolls:

Roll Width

Roll Length:

61 inches

52.82 lineal yards

UV Protector

This product has a UV protector in all its colors.

Special Additives

This product in white and beige have fungus retardant (biocide), which can be incorporated into the full range of colors as requested

Packaging Specifications:

Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping

The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).

This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.

Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.

To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. for more information please call us, toll free (866) 973 7185

Non Controlled Document