

Specification sheet FF 20

Base fabric			
Style:	Plain weaving: 14 x 14 1000 Denier	Fiber:	Polyester
Count:	14 X 14 thread/inc ó 5.5 x 5.5 thread/cm	Denier:	1000

Properties:		Unit:	Specification:	Unit:	Specification:
Weight		Gr/m²	680 ± 3 %	Oz/Yd²	20 ± 3 %
Breaking Strength (1)	Warp	Kgf/cm²	37 ± 5 %	Lb/in ²	207 ± 5 %
	Weft	Kgf/cm²	32 ± 5 %	Lb/in²	179 ± 5 %
Tear Strength (1)	Warp	Kgf	42 ± 5 %	Lb	93 ± 5 %
	Weft	Kgf	41 ± 5 %	Lb	90 ± 5 %
Flammability Testing		NFPA-701	The specimen shall not continue to flame for more than two seconds		
Adhesion ⁽²⁾		Kgf/cm²	> 3.5	Lb/in²	> 19.6
Thickness ⁽²⁾		mm	.60 ± 5 %	in	.024 ± 5 %
Opacity ⁽²⁾		809	% 80%		

Physical Specifications for rolls:	Roll Width	Roll Length:
	61 inches	56.44 lineal yards

UV Protector

This product has a UV protector in all its colors.

Special Additives

This product in white and beige have anti mildew (biocide), which can be incorporated into the full range of special order colors. It has flame retardant in all variants except the black.

Packaging Specifications:

Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping

The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).

This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.

Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.

To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. fort more information please call us, toll free (866) 973 7185

Non Controlled Document