

Specification sheet MK 10

Autorizated by:
Control Number:
Consecutive:

Emission Date:

Page:

Ma. Esther Sánchez Quality Assurement QA-SS-006

1

19-July-2019 1 de 1

Base fabric

Style:	Plain weaving: 20 x 20 1000 Denier	Fiber:	Polyester
Count:	20 X 20 thread/inc ó 5.5 x 5.5 thread/cm	Denier:	1000

Properties:		Unit:	Specification:	Unit:	Specification:
Weight		Gr/m²	355 ± 4 %	Oz/Yd²	10 ± 4 %
Breaking Strength (1)	Warp	Kgf/cm²	47 ± 5 %	Lb/in²	263 ± 5 %
	Weft	Kgf/cm²	38 ± 5 %	Lb/in²	213 ± 5 %
Tear Strength (1)	Warp	Kgf	52 ± 5 %	Lb	115 ± 5 %
	Weft	Kgf	47 ± 5 %	Lb	104 ± 5 %
Adhesion ⁽²⁾		Kgf/cm²	> 1.3	Lb/in²	> 7.3
Thickness ⁽²⁾		mm	.37 ± 5 %	in	.015 ± 5 %

Physical Specifications for rolls:	Roll Width	Roll Length:
	61 inches	100 lineal yards

UV Protector

This product has a UV protector in all its colors.

Packaging Specifications:

Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping

The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).

This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.

Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.

To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. fort more information please call us, toll free (866) 973 7185

Non Controlled Document