



**PLASTIC  
FABRIC  
SOLUTIONS**  
by MEGAPLAST

## Specification sheet MS 80

<b>Autorized by:</b>	Ma. Esther Sánchez
<b>Control Number:</b>	Quality Assurance QA-SS-012
<b>Consecutive:</b>	0
<b>Emission Date:</b>	26-July-2021
<b>Page:</b>	1 de 1

### Base fabric

<b>Style:</b>	Weft Insertion: 11 x 11 1000 Denier	<b>Fiber:</b>	Polyester
<b>Count:</b>	11 X 11 thread/inc ó 4.3 x 4.3 thread/cm	<b>Denier:</b>	1000

Properties:	Unit:	Specification:	Unit:	Specification:
<b>Weight</b>	Gr/m <sup>2</sup>	230 ± 3 %	Oz/Yd <sup>2</sup>	7 ± 3 %
<b>Breaking Strength (1)</b>	<b>Warp</b>	Kgf/cm <sup>2</sup>	Lb/in <sup>2</sup>	123 ± 5 %
	<b>Weft</b>	Kgf/cm <sup>2</sup>	Lb/in <sup>2</sup>	106 ± 5 %
<b>Tear Strength (1)</b>	<b>Warp</b>	Kgf	Lb	35 ± 5 %
	<b>Weft</b>	Kgf	Lb	33 ± 5 %
<b>Adhesion (2)</b>	Kgf/cm <sup>2</sup>	> 2.0	Lb/in <sup>2</sup>	> 11.2
<b>Thickness (2)</b>	mm	.38 ± 5 %	in	.015 ± 5 %

### Physical Specifications for rolls:

**Roll Width**

**Roll Length:**

61 inches

52.82 lineal yards

### UV Protector

*This product has a UV protector in all its colors.*

### Packaging Specifications:

*Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping*

*The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).*

*This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.*

*Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.*

*To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. for more information please call us, toll free (866) 973 7185*

**Non Controlled Document**