



DF Vinyl Coated Polyester
38 oz

STRENGTH AND DURABILITY

Perfect for applications that require strength and durability.

TECHNICAL SPECIFICATIONS



PLAIN WEAVING
14x14 thread count/in
1000D



BREAKING STRENGTH
WARP: 207 lb/in \pm 5%
WEFT: 202 lb/in \pm 5%



TEAR STRENGTH
WARP: 55 lb \pm 5%
WEFT: 51 lb \pm 5%



WEIGHT
38 oz/yd² \pm 4%



ADHESION
>16.8 lb/in



ROLL
61" x 33.16 yd



THICKNESS
.0394 in \pm 3%

APPLICATIONS

- Water Reservoirs
- Debris Tarp
- Siders
- Asphalt Tarps
- Dock Seals
- and more...

AVAILABLE COLORS



Black



Ask for new color development.

*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.



TOLL FREE (866) 973 7185



salesteam@plasticfabrics.com



www.plasticfabrics.com



/Plastic Fabric Solutions INC



MANAGEMENT SYSTEM²⁰¹⁵

ISO 9001

BICERT

Certificate No: SG 20201851.01

*Images shown are for reference of the final product, Plastic Fabric Solutions does not certify they represent our final product. - Optimal usage and maintenance are responsibility of the final user to preserve product integrity and utility. - Validity 2023-2024