



# FIRE RESISTANT CERTIFICATE

Light weight PVC coated fabric

## TECHNICAL SPECIFICATIONS



**WEFT INSERTION**  
9x9 thread count/in  
1000D



**BREAKING STRENGTH**  
WARP: 118 lbf/in  $\pm$  5%  
WEFT: 112 lbf/in  $\pm$  5%



**TEAR STRENGTH**  
WARP: 49 lbf  $\pm$  5%  
WEFT: 44 lbf  $\pm$  5%



**WEIGHT**  
12 oz/yd<sup>2</sup>  $\pm$  3%



**ADHESION**  
>11.2 lb/f



**ROLL**  
61" x 54.68 yd



**THICKNESS**  
.012 in  $\pm$  5%

## APPLICATIONS

- Industrial Curtains
- Awnings
- Tents

## AVAILABLE COLORS



Antimildew (biocide) in white and beige color, it's flame resistant based on CSFM certification F-88801



Ask for new color development.

\*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.

 **TOLL FREE (866) 973 7185**

 **salesteam@plasticfabrics.com**

 **www.plasticfabrics.com**

   **/Plastic Fabric Solutions INC**



Certificate No: SG 20201851.01

\*Images shown are for reference of the final product, Plastic Fabric Solutions does not certify they represent our final product. - Optimal usage and maintenance are responsibility of the final user to preserve product integrity and utility. - Validity 2023-2024