



# IDEAL FOR TENT MANUFACTURING

Its light weight design allows for easy of handling and installation.

## TECHNICAL SPECIFICATIONS



**WEFT INSERTION**  
9X9 thread count/in  
1000D



**BREAKING STRENGTH**  
WARP: 129 lbf/in  $\pm$  5%  
WEFT: 112 lbf/in  $\pm$  5%



**TEAR STRENGTH**  
WARP: 49 lbf  $\pm$  5%  
WEFT: 49 lbf  $\pm$  5%



**WEIGHT**  
16 oz/yd<sup>2</sup>  $\pm$  4%



**ADHESION**  
>11.2 lb/f



**ROLL**  
61" x 52.8 yd



**THICKNESS**  
.015 in  $\pm$  5%

## APPLICATIONS

- Tent curtains
- Awnings
- Small party tents

## AVAILABLE COLORS



Ask for new color development.  
\*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.

Antimildew (biocide) and it's flame resistant.



**TOLL FREE** (866) 973 7185



salesteam@plasticfabrics.com



www.plasticfabrics.com



/Plastic Fabric Solutions INC



MANAGEMENT SYSTEM <sup>2015</sup>

**ISO 9001**

**BICERT**

Certificate: SG 20171851