



**FF** Vinyl Coated Polyester  
20 oz

# FOR YOUR EVENT BUSINESS

Designed for small tension structures and tents manufacturing.

## TECHNICAL SPECIFICATIONS



**PLAIN WEAVING**  
14x14 thread count/in  
1000D



**BREAKING STRENGTH**  
WARP: 207 lb/in  $\pm$  5%  
WEFT: 179 lb/in  $\pm$  5%



**TEAR STRENGTH**  
WARP: 93 lb  $\pm$  5%  
WEFT: 90 lb  $\pm$  5%



**WEIGHT**  
20 oz/yd<sup>2</sup>  $\pm$  3%



**ADHESION**  
>19.6 lb/f



**ROLL**  
61" x 56.4 yd



**THICKNESS**  
.024 in  $\pm$  5% inches

## APPLICATIONS

- Curtains
- Party Tents
- Awnings
- Fabric Buildings
- Tarps
- Silos

## AVAILABLE COLORS

White

Antimildew (biocide) and it includes flame resistant.



Ask for new color development.

\*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.

 **TOLL FREE (866) 973 7185**

 **salesteam@plasticfabrics.com**

 **www.plasticfabrics.com**

   **/Plastic Fabric Solutions INC**



Certificate No: SG 20201851.01

\*Images shown are for reference of the final product, Plastic Fabric Solutions does not certify they represent our final product. - Optimal usage and maintenance are responsibility of the final user to preserve product integrity and utility. - Validity 2023-2024