



FM Vinyl Coated Polyester
8 oz

YOUR BEST OPTION FOR STRUCTURAL FUMIGATION

Ultra lightweight PVC Coated Fabric ideal
for structural fumigation tents
manufacturing

TECHNICAL SPECIFICATIONS



PLAIN WEAVING
34X28 thread count/in
500 D



BREAKING STRENGTH
WARP: 207 lb/in \pm 5%
WEFT: 129 lb/in \pm 5%



TEAR STRENGTH
WARP: 68 lb \pm 5%
WEFT: 71 lb \pm 5%



WEIGHT
8 oz/yd² \pm 5%



ADHESION
>6.7 lb/in



ROLL
61" x 100.88 yd



THICKNESS
.010 in \pm 5% inches



AVAILABLE COLORS



Yellow



Orange



Wine



Black



Red



Forest Green



Dark Green



Royal Blue



Navy Blue



Light Blue



Dark Gray



White

*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.



TOLL FREE (866) 973 7185



salesteam@plasticfabrics.com



www.plasticfabrics.com



/Plastic Fabric Solutions INC



MANAGEMENT SYSTEM²⁰¹⁵

ISO 9001

BICERT

Certificate: SG 20201851.01