



MF Vinyl Coated Polyester
24 oz

FIRE RETARDANT CERTIFICATE

Blockout PVC coated fabric

TECHNICAL SPECIFICATIONS



PLAIN WEAVING
14x14 thread count/in
1300D



BREAKING STRENGTH
WARP: 246 lbf/in \pm 5%
WEFT: 202 lbf/in \pm 5%



TEAR STRENGTH
WARP: 110 lbf \pm 5%
WEFT: 115 lbf \pm 5%



WEIGHT
24 oz/yd² \pm 3%



ADHESION
>14 lb/in



ROLL
61" x 52.8 yd



THICKNESS
.028 in \pm 5%

APPLICATIONS

- Industrial Curtains
- Structures
- Awnings
- Cirque
- Tents
- Fabric buildings

AVAILABLE COLORS



Antimildew (biocide) in white and beige color, it's flame resistant based on CSFM certification F-88801



Ask for new color development.

*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.



TOLL FREE (866) 973 7185



salesteam@plasticfabrics.com



www.plasticfabrics.com



/Plastic Fabric Solutions INC



MANAGEMENT SYSTEM ²⁰¹⁵
ISO 9001
BICERT

Certificate No: SG 20201851.01

*Images shown are for reference of the final product, Plastic Fabric Solutions does not certify they represent our final product. - Optimal usage and maintenance are responsibility of the final user to preserve product integrity and utility. - Validity 2023-2024