



**PLASTIC
FABRIC
SOLUTIONS**
by MEGAPLAST

Specification sheet MK 14

Authorized by:	Ma. Esther Sánchez Quality Assurance
Control Number:	QA-SS-007
Consecutive:	0
Emission Date:	26-July-2021
Page:	1 de 1

Base fabric

Style:	Plain weaving: 20 x 20 1000 Denier	Fiber:	Polyester
Count:	20 X 20 thread/inc ó 5.5 x 5.5 thread/cm	Denier:	1000

Properties:	Unit:	Specification:	Unit:	Specification:
Weight	Gr/m ²	470 ± 3 %	Oz/Yd ²	14 ± 3 %
Breaking Strength (1)	Warp	Kgf/cm ²	Lb/in ²	280 ± 5 %
	Weft	Kgf/cm ²	Lb/in ²	213 ± 5 %
Tear Strength (1)	Warp	Kgf	Lb	106 ± 5 %
	Weft	Kgf	Lb	84 ± 5 %
Adhesion (2)	Kgf/cm ²	> 1.3	Lb/in ²	> 7.3
Thickness (2)	mm	.42 ± 5 %	in	.017 ± 5 %

Physical Specifications for rolls:	Roll Width	Roll Length:
	61 inches	100 lineal yards

UV Protector

This product has a UV protector in all its colors.

Packaging Specifications:

Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping

The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).

This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.

Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.

To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. for more information please call us, toll free (866) 973 7185

Non Controlled Document



**PLASTIC
FABRIC
SOLUTIONS**
by MEGA PLAST

Specification sheet MK 16

Autorized by:	Ma. Esther Sánchez
Control Number:	Quality Assurance QA-SS-014
Consecutive:	0
Emission Date:	26-July-2021
Page:	1 de 1

Base fabric

Style:	Plain weaving: 20 x 20 1000 Denier	Fiber:	Polyester
Count:	20 X 20 thread/inc ó 5.5 x 5.5 thread/cm	Denier:	1000

Properties:	Unit:	Specification:	Unit:	Specification:
Weight	Gr/m ²	540 ± 3 %	Oz/Yd ²	16 ± 3 %
Breaking Strength (1)	Warp	Kgf/cm ²	Lb/in ²	280 ± 5 %
	Weft	Kgf/cm ²	Lb/in ²	213 ± 5 %
Tear Strength (1)	Warp	Kgf	Lb	123 ± 5 %
	Weft	Kgf	Lb	95 ± 5 %
Adhesion (2)	Kgf/cm ²	> 1.3	Lb/in ²	> 7.3
Thickness (2)	mm	.48 ± 5 %	in	.019 ± 5 %

Physical Specifications for rolls:

Roll Width

Roll Length:

61 inches

49.38 lineal yards

UV Protector

This product has a UV protector in all its colors.

Packaging Specifications:

Rolls wrapped individually in plastic film 0.08 mm, core windings in 0.144 "thick. Bulk shipping

The information presented here represent average values based on our own research under the reference ASTM D-751 (1) and internal methods (2).

This specification sheet does not constitute a warranty, so you do not release the customer to make their own tests, examinations and tests.

Customer assumes full responsibility for the final application of the product, which MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. is exempt from any liability arising from it.

To MEMBRANAS PLASTICAS INTERNACIONALES S.A. DE C.V. (Plastic Fabric Solutions INC) the improvement of our products is essential, for this reason we reserve the right to make changes without notice. for more information please call us, toll free (866) 973 7185

Non Controlled Document