



**F2** Vinyl Coated Polyester  
18 oz

# TRANSPARENT PVC COATED FABRIC

Designed for industrial curtain and tent sidewall manufacturing.

## TECHNICAL SPECIFICATIONS



**WEFT INSERTION**  
11X11 thread count/in  
1000 D



**BREAKING STRENGTH**  
WARP: 151 lb/in  $\pm$  5%  
WEFT: 157 lb/in  $\pm$  5%



**TEAR STRENGTH**  
WARP: 49 lb  $\pm$  5%  
WEFT: 68 lb  $\pm$  5%



**WEIGHT**  
18 oz/yd<sup>2</sup>  $\pm$  3%



**ADHESION**  
>19.6 lb/in



**ROLL**  
61" x 52.8 yd



**THICKNESS**  
.022 in  $\pm$  5% inches

## APPLICATIONS

- Curtains
- Bulkhead
- Window
- Awnings
- Tent
- and more...
- Tarps
- Skylight

## AVAILABLE COLORS

Transparent

Ask for new color development.

\*We assure the final product will meet the technical specifications shown on this brochure even though its appearance may vary on individual batches due to continuous production improvement.



**TOLL FREE** (866) 973 7185



salesteam@plasticfabrics.com



www.plasticfabrics.com



/Plastic Fabric Solutions INC



Certificate No: SG 20231851.01

Images shown are for reference of the final product, Plastic Fabric Solutions Inc. does not certify they represent our final product. Optimal usage and maintenance are responsibility of the final user to preserve product integrity and utility. Valid from 2024 - 2025.